



Overview

Model Name	Power-Saving Back-UPS Pro 900, 230V, Schuko
Includes	Telephone Cable , User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Albania , Algeria , Andorra , Angola , Austria , Belgium , Bosnia And Herzegovina , Bulgaria , Burkina Faso , Cameroon , Central African Republic , Chad , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cote D'Ivoire , Croatia , Estonia , Finland , Gabon , Germany , Greece , Guinea , Hungary , Iceland , Italy , Latvia , Lithuania , Luxembourg , Macedonia , Madagascar , Mali , Mauritania , Mauritius , Mayotte , Morocco , Netherlands , Niger , Norway , Portugal , Romania , Senegal , Slovenia , Spain , Sweden , Togo , Tunisia , Turkey

Output

Output Power Capacity	540 Watts / 900 VA
Max Configurable Power (Watts)	540 Watts / 900 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/-1 Hz
Output Frequency (sync to mains)	Line Interactive
Output Connections	(2) Schuko CEE 7 (Surge Protection) , (3) Schuko CEE 7 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	Schuko CEE 7/7P
Cord Length	1.52 meters
Input voltage range for main operations	176 - 294 V
Input voltage adjustable range for mains operation	156 - 300V

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	8 hour(s)
Replacement Battery	APCRBC123
RBC Quantity	1

Communications & Management

Interface Port(s)	Optional Simple Signalling RS232 cable , USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	613 Joules
Filtering	Full time multi-pole noise filtering :10% of IEEE surge let-through : zero clamping response time: instantaneous
Data Line Protection	RJ-11 Modem/Fax/DSL protection (two wire single line) , RJ45 10/100/1000 Base-T Ethernet protection

Physical

Maximum Height	250.0 mm
Maximum Width	100.0 mm
Maximum Depth	382.0 mm
Net Weight	10.73 kg
Shipping Weight	12.41 kg
Shipping Height	487.0 mm
Shipping Width	225.0 mm
Shipping Depth	337.0 mm
Units per Pallet	30.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Approvals	BSI 1363 , CE , GOST , NEMKO
Standard warranty	2 years repair or replace , 3 years repair or replace for European Union countries
Equipment protection policy	Lifetime : 150000 Euros , Lifetime : 200000 AUD , Lifetime : 75000 GBP

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs