

## ALARM-S201-WE Wireless Sounder Indoor



- Adjustable volume for alarm, arming, disarming events
- 4 kinds of alarm sounds: FIRE, PANIC, MEDICAL and INTRUSION alarm
- Up to 95 dB at 1 m distance
- Frequency hopping against jamming for reliable transmission

## ▪ Specification

<b>Communication</b>	
Transmission technology	868.0-868.6 MHz
Transmission range (free space)	Up to 1,600 m
Maximum effective radiated power (ERP)	25 mW max
Radio signal modulation	2GFSK
<b>Software features</b>	
Temperature indicator	Yes
<b>Indication</b>	
Indication method	Acoustic and LED
Sound volume level	Adjustable, 80–95 dB at a distance of 1 m
Alarm duration	Adjustable, 10 s–15 min
<b>Hardware features</b>	
Tamper-Proof	Yes
<b>Electrical characteristics</b>	
Power supply	4 × AA batteries
Power consumption	max current: 400 mA quiescent current: 35 uA
Battery life	Up to 2 years (standby time)
<b>General</b>	
Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
Operation humidity	10% to 90%
Dimension(WxHxD)	93 × 93 × 33.7 mm
Weight	117 g

## ▪ Available Model

ALARM-S201-WE

## HiLook

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

