

ALARM-KF201-WE Wireless Keyfob



- Remote arming and disarming
- Configurable I and II buttons can provide more useful functions
- Frequency hopping against jamming for reliable transmission

▪ Specification

| Communication | |
|--|---|
| Transmission technology | 868.0-868.6 MHz |
| Transmission range (free space) | Up to 900 m |
| Maximum effective radiated power (ERP) | 10 mW max |
| Radio signal modulation | 2GFSK |
| Hardware features | |
| Number of buttons | Four buttons |
| Configuration of buttons | I key II key |
| Electrical characteristics | |
| Power supply | 1 × CR2032 battery |
| Power consumption | max current: 40 mA quiescent current: 0.4 uA |
| Battery life | Up to 2 years (standby time) |
| General | |
| Operation temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| Operation humidity | 10% to 90% |
| Dimension (W×H×D) | 35 × 64 × 11.2 mm |
| Weight | 15 g |

▪ Available Model

ALARM-KF201-WE

HiLook

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

