

Product datasheet

Specifications



APC Back-UPS Pro, 1500VA/865W,
Tower, 230V, 6x CEE 7/7 Schuko
outlets, Sine Wave, AVR, LCD, User
Replaceable Battery

BR1500G-GR

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
rated power in W	865 W
rated power in VA	1500 VA
Product or component type	Uninterruptible power supply (UPS)
output connection type	3 Schuko CEE 7 3 Schuko CEE 7 surge
Cable length	1.5 m

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery charger power	23 W rated
Battery life	3...5 year(s)
Replacement battery	APCRBC124
Extended runtime	0

General

Provided equipment	telephone cable user manual USB cable warranty card
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Height	30.1 cm
Width	11.2 cm
Depth	38.2 cm
Net weight	13 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50 Hz +/- 1 Hz 60 Hz +/- 1 Hz
Input voltage limits	156...300 V adjustable 176...294 V

Output

Maximum configurable power in W	865 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	1500 VA
Transfer time	10 ms typical : 12 ms maximum

Conformance

Product certifications	BSI 1363 CE NEMKO
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	45 dBA

Communications & Management

control panel	Multifunction LCD status and control console
---------------	--

Surge Protection and Filtering

Surge energy rate	441 J
Data line protection	RJ11 modem/fax/DSL protection (two wire single line)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39 cm
Package 1 Width	49 cm
Package 1 Length	23.5 cm
Package 1 Weight	13.8 kg
SCC14	10731304286872

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

Compliant with Exemptions

SCIP Number

019b51cf-d7f1-4f06-ac85-1378fc94c7aa

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Use Again

Repack and remanufacture


Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back

Yes