

## DS-2CD1327G2H-LIUF/S(L)(RB)

2 MP ColorVu with Smart Hybrid Light Fixed Turret Network Camera

ColorVu



- High quality imaging with 2 MP resolution
- 24/7 colorful imaging
- Support Person and Vehicle Detection
- Smart Hybrid Light: advanced technology with long range cover
- Provide real-time security via built-in two-way audio and strobe light alarm
- Efficient H.265+ compression technology
- Support on-board storage up to 512 GB (SD card slot)
- Water and dust resistant (IP67)

## ▪ Specification

| Camera                      |   |
|-----------------------------|---|
| Image Sensor                | 1/2.8" Progressive Scan CMOS  |
| Max. Resolution             | 1920 × 1080   |
| Min. Illumination           | Color: 0.001 Lux @ (F1.0, AGC ON), 0 Lux with light   |
| Shutter Time                | 1/3 s to 1/100,000 s  |
| Day & Night                 | IR cut filter   |
| Angle Adjustment            | Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°  |
| Lens                        |   |
| Lens Type                   | Fixed focal lens, 2.8 and 4 mm optional   |
| Focal Length & FOV          | 2.8 mm, horizontal FOV 106°, vertical FOV 56°, diagonal FOV 129°<br>4 mm, horizontal FOV 88°, vertical FOV 47°, diagonal FOV 103° |
| Lens Mount                  | M12   |
| Iris Type                   | Fixed   |
| Aperture                    | F1.0  |
| DORI                        |   |
| DORI                        | 2.8 mm, D: 44 m, O: 17 m, R: 8 m, I: 4 m<br>4 mm, D: 53 m, O: 21 m, R: 10 m, I: 5 m   |
| Illuminator                 |   |
| Supplement Light Type       | IR, White Light   |
| Supplement Light Range      | Up to 30 m  |
| Smart Supplement Light      | Yes   |
| IR Wavelength               | 850 nm  |
| Video                       |   |
| Main Stream                 | 50 Hz: 25 fps (1920 × 1080, 1280 × 720)<br>60 Hz: 30 fps (1920 × 1080, 1280 × 720)  |
| Sub-Stream                  | 50 Hz: 25 fps (640 × 480, 640 × 360)<br>60 Hz: 30 fps (640 × 480, 640 × 360)  |
| Video Compression           | Main stream: H.265+/H.265/H.264+/H.264,<br>Sub-stream: H.265/H.264/MJPEG  |
| Video Bit Rate              | 32 Kbps to 8 Mbps   |
| H.264 Type                  | Baseline Profile, Main Profile, High Profile  |
| H.265 Type                  | Main Profile  |
| Bit Rate Control            | CBR, VBR  |
| Region of Interest (ROI)    | 1 fixed region for main stream  |
| Audio                       |   |
| Audio Type                  | Mono sound  |
| Audio Compression           | G.711/G.722.1/G.726/MP2L2/PCM/AAC-LC  |
| Audio Bit Rate              | 64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/16 to 64 Kbps (AAC-LC)                                   |
| Audio Sampling Rate         | 8 kHz/16 kHz  |
| Environment Noise Filtering | Yes   |
| Network                     |   |
| Protocols                   | TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, RTCP, NTP, IPv4, IPv6, IGMP, UDP, QoS, FTP, SMTP, UPnP                                  |
| Simultaneous Live View      | Up to 6 channels  |

|                                  |  |
|----------------------------------|--|
| API                              | ONVIF (Profile S, Profile G, Profile T), ISAPI, SDK  |
| Security                         | Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address) |
| User/Host                        | Up to 32 users<br>3 user levels: administrator, operator, and user   |
| Client                           | iVMS-4200, Hik-Connect   |
| Web Browser                      | Plug-in required live view: IE 10, IE 11,<br>Local service: Chrome 57.0+, Firefox 52.0+, Edge 89+  |
| <b>Image</b>                     |  |
| Image Settings                   | Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser  |
| Day/Night Switch                 | Day, Night, Auto, Schedule   |
| Wide Dynamic Range (WDR)         | Digital WDR  |
| SNR                              | ≥ 52 dB  |
| Image Enhancement                | BLC, HLC, 3D DNR   |
| Privacy Mask                     | 4 programmable polygon privacy masks   |
| <b>Interface</b>                 |  |
| Ethernet Interface               | 1 RJ45 10 M/100 M self-adaptive Ethernet port  |
| On-Board Storage                 | Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB  |
| Built-in Microphone              | Yes, 1 built-in microphone   |
| Built-in Speaker                 | 1 built-in speaker,<br>Max. power consumption: 2 W, max. sound pressure level: 10 cm: 101 dB.  |
| Reset Key                        | Yes  |
| <b>Event</b>                     |  |
| Basic Event                      | Motion detection (support alarm triggering by specified target types (person and vehicle)), video tampering alarm, exception   |
| Linkage                          | Upload to memory card, upload to FTP, trigger recording, notify surveillance center, send email, trigger capture   |
| <b>General</b>                   |  |
| Power                            | 12 VDC ± 25%, 0.50 A, max. 6.0 W, Ø5.5 mm coaxial power plug, reverse polarity protection,<br>PoE: IEEE 802.3af, Class 3, max. 7.2 W   |
| Material                         | Metal & Plastic  |
| Dimension                        | Ø110 mm × 93 mm (Ø4.33" × 3.66")   |
| Package Dimension                | 150 mm × 150 mm × 141 mm (5.91" × 5.91" × 5.55")   |
| Weight                           | Approx. 400 g (0.9 lb.)  |
| With Package Weight              | Approx. 646 g (1.4 lb.)  |
| Storage Conditions               | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)  |
| Startup and Operating Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)  |
| Language                         | English, Ukrainian   |
| General Function                 | Heartbeat, mirror, flash log, password reset via email, password protection, anti-banding  |
| Flashing Light                   | /SRB model: Red and Blue Light<br>/SL model: White Light   |

| Approval    |  |
|-------------|--|
| EMC         | CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021               |
| Safety      | UL: UL 62368-1,<br>CB: IEC 62368-1: 2014+A11,<br>CE-LVD: EN 62368-1: 2014/A11: 2017,<br>BIS: IS 13252 (Part 1): 2010/IEC 60950-1: 2005 |
| Environment | CE-RoHS: 2011/65/EU,<br>WEEE: 2012/19/EU,<br>Reach: Regulation (EC) No 1907/2006   |
| Protection  | IP67: IEC 60529-2013   |

## ▪ Typical Application

Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.

This model has NO SPECIFIC PROTECTION.

| Level                  | Description  |
|------------------------|--|
| Top-level protection   | Hikvision products at this level are equipped for use in areas where professional anti-corrosion protection is a must. Typical application scenarios include coastlines, docks, chemical plants, and more.   |
| Moderate protection    | Hikvision products at this level are equipped for use in areas with moderate anti-corrosion demands. Typical application scenarios include coastal areas about 2 kilometers (1.24 miles) away from coastlines, as well as areas affected by acid rain. |
| No specific protection | Hikvision products at this level are equipped for use in areas where no specific anti-corrosion protection is needed.  |

## ▪ Available Model


DS-2CD1327G2H-LIUF/SL(2.8mm)

DS-2CD1327G2H-LIUF/SL(4mm)

DS-2CD1327G2H-LIUF/SRB(2.8mm)

DS-2CD1327G2H-LIUF/SRB(4mm)







▪ **Dimension**










Unit: mm (inch)

▪ **Accessory**

▪ **Optional**

| DS-1272ZJ-110B<br>Wall mount  | DS-1272ZJ-110<br>Wall mount   | DS-1271ZJ-110<br>Pendant Mount  | DS-1275ZJ-SUS<br>Vertical pole mount  | DS-1276ZJ-SUS<br>Corner mount   |
|---|---|---|---|---|
|  |  |  |  |  |
|  |  |  |  |  |

| DS-1280ZJ-S<br>Junction box   | DS-1281ZJ-S<br>Inclined ceiling mount   | DS-2280ZJ-WA110<br>Junction box   | DS-2210ZJ-WA-110<br>Pendant Mount   | DS-2200ZJ-WA-110<br>Wall mount  |
|---|---|---|---|---|
|    |  |  |  |  |
|    |  |  |   |  |
| <b>DS-2200ZJ-WAJ-110<br/>Wall mount</b>   |   |   |   |   |
|  |   |   |   |   |
|  |   |   |   |   |

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

