

DS-2CE56C5T-AVFIR HD720p Indoor Varifocal IR Dome Camera


TurboHD™



Key Features

- 720p Video Output
- 2.8 mm to 12 mm Varifocal Lens
- True Day/Night
- OSD Menu, 3D DNR, Smart IR
- Up to 100 Feet IR Distance
- UTC Function (Hikvision-C Protocol)
- 24 VAC/12 VDC

Dimensions



Accessories



Video Balun
DS-1H18



In-Ceiling Mount
RCM-3



PC130
Pendant Cap

Order Model

DS-2CE56C5T-AVFIR

DS-2CE56C5T-AVFIR	
Camera	
Image Sensor	1.3 MP CMOS
HD-TVI Resolution	1280 x 720
Minimum Illumination	Color: 0.0014 @ f/1.4; B/W: 0 with IR
Shutter Speed	1/30 s to 1/50,000 s
Lens	2.8 mm to 12 mm @ f/1.4 Angle of view: 78° to 28°
Lens Mount	φ14
Angle Adjustment	Pan: 0° to 355°, tilt: 0° to 75°, rotation: 0° to 355°
Day/Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	720p @ 60 fps
HD Video Output	1 analog HD output
CVBS Output	1 Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62 dB
Menu Settings	
Automatic Exposure	Globe AE/DWDR
AGC	Low/middle/high/off
Slow Shutter	Supported
White Balance	Auto/manual
D/N Mode	Color/BW/SMART IR
3D DNR	Low/middle/high/off
Motion Detection	Supported, maximum 4 zones
Privacy Mask	On/off, maximum 8 zones
UTC Function	Supported
Image Settings	Digital Wide Dynamic Range, 3D Digital Noise Reduction, sharpness, brightness, digital zoom, mirror, reset
General	
Operating Conditions	-20° C to 60° C (-4° F to 140° F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24 VAC
Power Consumption	12 VDC: maximum 3.5 W 24 VAC: maximum 5 W
IR Range	100 feet
Communication	Up-the-Coax (need UTC controller) Protocol: Hikvision-C
Dimensions	Φ136 mm × 101 mm (Φ5.35" × 3.98")
Weight	380 g (0.84 lb.)