




Picture		
Model	Go Series G430	
Video & Audio	Image Sensor	1/3" CMOS Sensor
	Video Resolution	2880 x 1620 (5.0Megapixel) at 15 frames/sec
	Video Format	H.265
	Field of View	Fixed lens, Horizontal: 90°, Vertical: 47°, 110° diagonal
	Infrared Night Vision	up to 10 Meters (33ft) (LED: 2pcs/1.2W/850nm)
	Spotlight	2pcs/2.4W/6500K/
	Digital Zoom	16x digital zoom
	Audio	two-way audio
PIR Detection & Alerts	Smart Alarm	PIR detection/Human Detection/Vehicle Detection/
	PIR Detecting Dis-	Adjustable up to 10m (33 ft)
	PIR Detecting Angle	120° horizontal
	Audio Alert	Customized verbal alerts
	Recording	Motion Triggered Recording
	Other Alerts	Instant email alerts and push notifications
3G/4G	Frequency Bands	LTE FDD: B1/B3/B7/B8/B20/B28A
		WCDMA: B1/B8
		LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71
		WCDMA: B2/B4/B5
		LTE FDD: B1/B3/B5/B7/B8/B28
		LTE TDD: B40
	Transmission Data	WCDMA: B1/B5/B8
		LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)
LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL)		
HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL)		
Power	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar	Reolink Solar Panel
	DC Power	5V/2A USB power adaptor
Storage	Local Storage	Supports up to 128GB micro SD card
	Cloud Storage	Supports Reolink Cloud
Smart Home	Smart Home	Works with Google Assistant
Working Environment	Operating Temperature	-10 to 55° C (14° to 131° F)
	Weather Resistance	IP64 Weatherproof
Size & Weight	Size	Φ98 x 122mm (Φ3.7 x 4.4 in)
	Weight (Battery in-	485 g (17.1 oz)
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/