




Reolink Innovation Limited

Picture			
Model	Duo Series G750		
Video & Audio	Image Sensor	1/3" CMOS Sensor	
	Video Resolution	4608x1728 (8.0Megapixel) at 15 frames/sec	
	Video Format	H.265	
	Field of View	Horizontal: 170° ; Vertical: 50°	
	Infrared Night Vision	30 Meters (LED: 6pcs/20mil/850nm)	
	Color Night Vision	Spotlight: 8pcs/4.4W/6500K/440 Lumens	
	Digital Zoom	6x digital zoom	
	Audio	two-way audio	
PIR Detection & Alerts	Smart Alarm	PIR Detection/Human Detection/Vehicle Detection/Pet Detection	
	PIR Detecting Distance	Adjustable up to 10m (33 ft)	
	PIR Detecting Angle	170° horizontal	
	Audio Alert	Customized verbal alerts	
	Recording	Motion Triggered Recording	
	Other Alerts	Instant email alerts and push notifications	
3G/4G	Frequency Bands	Europe	LTE FDD: B1/B3/B7/B8/B20/B28A
		WCDMA: B1/B8	
		America	LTE FDD: B2/B4/B12
		WCDMA: B2/B4/B5	
		Australia	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28
		LTE TDD: B40	
	Transmission Data	WCDMA: B1/B2/B5/B8	
		LTE FDD: Max 10Mbps (DL), Max 5Mbps (UL)	
		LTE TDD: Max 8.96Mbps (DL), Max 3.1Mbps (UL)	
		HSPA+: Max 42Mbps (DL), Max 5.76Mbps (UL)	
Power	Battery	10400mAh rechargeable battery (Battery life varies based on settings, usage & temperature)	
	Solar	Reolink Solar Panel 2	
	DC Power	5V/2A USB Type-C	
Storage	Local Storage	Supports up to 128GB micro SD card	
	Cloud Storage	Supports Reolink Cloud	
Working Environment	Operating Temperature	-10 to 55° C (14° to 131° F)	
	Weather Resistance	IP66 Weatherproof	
Size & Weight	Size	228x 132x 120 mm	
	Weight	900g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/	